

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Eurolight

Supplier's address: Eurolight, Klaipėdos g. 79A, LT-37106 Panevezys, LT

Model identifier: SL-100W

Type of light source:

| | | | |
|---|-----|---------------------------------|-----|
| Lighting technology used: | LED | Non-directional or directional: | DLS |
| Light source cap-type (or other electric interface) | DLS | | |
| Mains or non-mains: | MLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | No | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | No |


Product parameters

| Parameter | Value | Parameter | Value |
|--|-----------------------------|--|---|
| General product parameters: | | | |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer | 100 | Energy efficiency class | C |
| Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 14 000 in Narrow cone (90°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4 000 |
| On-mode power (P_{on}), expressed in W | 100,0 | Standby power (P_{sb}), expressed in W and rounded to the second decimal | - |
| Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 70 |
| Outer dimensions without separate control gear, lighting control | Height | 560 | Spectral power distribution in the range 250 nm to 800 nm, at full-load |
| | Width | 120 | |
| | Depth | 238 | |
| | | | See image in last page |


| | | | |
|---|-------------------|--|----------------|
| parts and non-lighting control parts, if any (millimetre) | | | |
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - |
| | | Chromaticity coordinates (x and y) | 0,379 0,382 |
| Parameters for directional light sources: | | | |
| Peak luminous intensity (cd) | 5 631 | Beam angle in degrees, or the range of beam angles that can be set | 75...155 |
| Parameters for LED and OLED light sources: | | | |
| R9 colour rendering index value | -35 | Survival factor | 0,90 |
| the lumen maintenance factor | 0,92 | | |
| Parameters for LED and OLED mains light sources: | | | |
| displacement factor (cos ϕ_1) | 0,90 | Colour consistency in McAdam ellipses | 6 |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | .. ^(b) | If yes then replacement claim (W) | - |
| Flicker metric (Pst LM) | 1,0 | Stroboscopic effect metric (SVM) | 0,4 |

(a) : not applicable;

(b) : not applicable;



Model placed on the Union market from 30/03/2022



EPREL registration number: 1172674

<https://eprel.ec.europa.eu/qr/1172674>

Supplier: UAB Siglus (Importer)

Website: <https://siglus.lt>

Customer care service:

Name: Eurolight

Website: eurolight.tech

Email: info@eurolight.tech

Phone: +37067091077

Address:

Klaipėdos g. 79A
LT-37106 Panevezys
Lithuania